

Regal Oak Cabinet Specifications

- ① Face Frames
Face Frames are $\frac{3}{4}$ " * $1\frac{1}{2}$ " Parallel Multi-ply hardwood Plywood, Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.
- ② Tops & Bottoms
Tops and bottom panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ " thick.
- ③ Toe Kicks
Toe kicks shall be $\frac{1}{2}$ " thick hardwood plywood.
- ④ End Panels
End panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$ ".
- ⑤ Adjustable Shelves
Adjustable shelves are $\frac{5}{8}$ " thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)
- ⑥ Back Panels
3 + 9 mm thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)
- ⑦ Shelf Clips
Shelf clips are 6mm bore with a fluted plastic $\frac{3}{8}$ " long stem and shelf lock mechanism. Shelves are adjustable on $2\frac{1}{2}$ " increments.
- ⑧ Doors
 $\frac{3}{4}$ " Solid Hardwood door styles with straight top veneer raised panel.

- ⑨ Hinges
Fully Concealed, 110 degree opening.
- ⑩ Drawer Boxes
 $\frac{1}{2}$ " plywood front, back and 2 sides with $\frac{3}{8}$ " drawer bottoms, screwed construction. (Exceeds industry standards.)
- ⑪ Drawer Glides
Side mount, epoxy coated, $\frac{3}{4}$ " extension. (Exceeds industry standards.)
- ⑫ Base Corner Brackets
High impact, injection molded plastic.
- ⑬ Hanging Strips
Hanging strip are $\frac{3}{4}$ " * $1\frac{1}{4}$ " hardwood.

