

## Sonona Wheat

## **Cabinet Specifications**

1 Face Frames

Face Frames are  $\frac{3}{4}$  \* 1  $\frac{1}{2}$  solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails.Frames are dadoed to received cabinet ends,top, and bottoms.

Tops & Bottoms

1/2" thick multi-ply hardwood plywood . Tops and bottoms are dadoed into the face frame and end panels. Base bottom

Toe Kicks

 $\frac{1}{2}$ " thick hardwood plywood.

4 End Panels

½"thick mutli-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ .

Adjustable Shelves

3/4" thick multi-ply hardwood Plywood. Edge banded with wood tapes.(Exceeds industry standards.)

6 Back Panels

½" thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)

on  $2\frac{1}{2}$  increments.

® Doors

3/4" thick & 3" width solid hard wood door stiles with flat central panel, Shaker style.

9 Hinges Full Overlay, Concealed, 110 degree opening, with soft closing dampers.

Drawer Boxes

3/4" solid hardwood front, back and 2 sides with 3/8" plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)

Drawer Glides

Soft Closing Undermount Full Extension Glides .. (Exceeds industry standards)

(12) Base Corner Brackets

High impact, Solid wooden blocks.

Hanging Strips

 $\frac{3}{4}$ "\*1 $\frac{1}{4}$ "hardwood.



